## **CLAIMS**

What is claimed is:

20

25

- 1. A wireless mobile phone comprising:
- a plurality of components coupled to each other to facilitate wireless telephony communication by a user;
  - a camera to facilitate real time taking of a photograph; and operating logic to receive the photograph and to operate the components depending on whether the user is successfully authenticated based at least in part on the photograph.
- 10 2. The wireless mobile phone of claim 1, wherein the operating logic further comprises logic to compare the photograph against a reference photograph.
  - 3. The wireless mobile phone of claim 1, wherein the operating logic further comprises logic to save the photograph as a reference photograph for authentication.
- 4. The wireless mobile phone of claim 1, wherein the wireless mobile phone further comprises a reader to facilitate provision of a reference photograph via an identity card, for use to authenticate the user.
  - 5. The wireless mobile phone of claim 4, wherein the reference photograph is stored in said identity card in a manner to be read by a reader selected from a reader group consisting of an electronic reader, an optical reader and a magnetic reader.
    - 6. The wireless mobile phone of claim 1, wherein the photograph is a photograph selected from the photograph group consisting of a photograph of the user' face, a photograph of a body part of the user, a photograph of an article, and a photograph of an object,
    - 7. In a wireless mobile phone, a method of operation comprising: taking a photograph;

WO 2004/089010 PCT/US2004/009780

authenticating the user using the photograph; and operating a plurality of components of the wireless mobile phone to facilitate wireless telephony communication by the user, in a manner that is dependent on whether the user was successful authenticated based at least in part on the photograph.

- 8. The method of claim 7, wherein the method further comprises comparing the photograph against a reference photograph.
- 9. The method of claim 7, wherein the method further comprises saving the photograph as a reference photograph for authentication.
- 10 10. The method of claim 7, wherein the method further comprises retrieving the reference photograph from an identity card.
  - 11. The method of claim 10, wherein said retrieving comprises a retrieving operation selected from the retrieving operation group consisting of an electronic retrieval operation, an optical retrieval operation, and a magnetic retrieval operation.
  - 12. The method of claim 10, wherein the photograph is a photograph selected from the photograph group consisting of a photograph of the user' face, a photograph of a body part of the user, a photograph of an article, and a photograph of an object,
- 20 13. A wireless mobile phone comprising:

5

15

25

a plurality of components coupled to each other to facilitate wireless telephony communication by a user, with the components being equipped to operate in at least a selected one of a first mode and a second mode; and

operating logic to operate the components in said first mode without authentication of the user, and to operate the components in said second mode if the user is successfully authenticated based at least in part on an authentication reference retrieved from an identity card.

WO 2004/089010 PCT/US2004/009780

14. The wireless mobile phone of claim 13, wherein the operating logic enables the components to provide first one or more functions while operating the components in said first mode, including retrieval of the authentication reference from the identity card, and further enables the components to provide second additional one or more functions, while operating the components in said second mode.

15. In a wireless mobile phone, a method of operation comprising: operating a plurality of components coupled to each other to facilitate wireless telephony communication by a user, in a first mode, prior to authenticating the user;

5

10

15

20

- retrieving an authentication reference from an identity card;
  receiving an input for authenticating the user; and
  operating the components in a second mode if the user is successfully
  authenticated based at least in part on the input and the retrieved authentication
  reference.
- 16. The method of claim 15, wherein said operating of the plurality of components in said first mode comprises enabling the components to provide first one or more functions, including retrieval of the authentication reference from the identity caard, and said operating of the plurality of components in said second mode comprises enabling the components to further provide second one or more functions.